

ANCILLARY PRODUCTS



'STACKER'

LOAD CAPACITIES:	200kgs (440lbs)
WEIGHT:	100kgs (220lbs)
CONSTRUCTION:	Stainless Steel
MAXIMUM HEIGHT:	1500mm (60")
MINIMUM HEIGHT:	100mm (4")
STRADDLE LEGS:	L x 485mm W x 490mm H x 90mm (L x 19" W x 19" H x 3.5")
LIFTING SPEED :	100mm(4")/sec
CHARGING VOLTAGE:	230V
BATTERY VOLTAGE:	24V
WHEELS:	2 fixed front wheels 80mm (3") 2 braking rear wheels 125mm (5")
CHARGER:	Stand alone

PALLET TRUCKS

CAPACITY:	2000kgs (4400lbs)
MIN. LOWERED FORK HEIGHT:	85mm(3.3")
FORK LENGTH:	1150mm (45")
WIDTH OVER FORKS:	520mm (20")
FORK WIDTH:	150mm(6")
NET WEIGHT:	75kg (165lbs)



HEAD OFFICE
Palamatic Handling Systems
 Cobnar Wood Close
 Chesterfield Trading Estate
 Chesterfield
 Derbyshire, S41 9RQ
 England
 Tel: +44 (0)1246 452054
 Fax: +44 (0)1246 451379
 Email: sales@palamatic.com
 Web: www.palamatic.com

Palamatic Handling USA Inc
 PO Box 2020
 West Chester
 PA19380

Tel: +1 610 701 6350
 Fax: +1 610 701 6354
 Email: tcarney@chesco.com
 Web: www.palamaticusa.com

Palamatic Handling Systems France
 Tel: +33 299 860622
 Fax: +33 299 860810

Palamatic Handling Systems India
 Tel: +91 80 5484733
 Fax: +91 80 5485119
 Email: scorpio@bgl.vsnl.net.in

Distributors in:

- | | |
|----------------|--------------|
| Australia | Malaysia |
| Belgium | New Zealand |
| Brazil | Norway |
| Canada | Portugal |
| Czech Republic | Singapore |
| Denmark | South Africa |
| France | Spain |
| Holland | Sweden |
| India | UAE |
| Ireland | USA |
| Italy | |

Palamatic's worldwide sales network ensures that our expertise works for the company and its operatives



Vacuum Tube Lifter handling 50kg (110lbs) reels supported from a stainless steel floor mounted support column with 3m (10') swing jib



Wall mounted swing jib arrangement and vacuum tube lifter handling sacks from a pallet into a sack tip booth.



Mobile Pillar Tipper handling plastic containers from pallet, inverting and placing onto a buck valve.



Stainless Steel Manipulator with weighing feature handling plastic drums from a filling head to a pallet.



Fixed or mobile tipping unit with 90°, 135° and 180° manual or powered turning options. Capacities to suit applications.



Low level manipulator lifting and inverting stainless steel vessels and feeding into washing machine.

Introduced by: