

LIFTING TROLLEY NEWTON 100

M4600000



Lifting Trolley Newton 100

Working efficiently means to work safely and comfortably. Use Newton 100 for handling goods up to 100kg. Fixed control unit, On/Off switch, battery indicator and a separate battery charger.



TnT Handling USA, Inc.

Ph: 610-701-6350

Fx: 610-701-6354

E-mail info@tnthandling.com , Web www.tnthandling.com

HALLINS

Lifting Trolley Newton 100

Working efficiently means to work safely and comfortably. Use Newton 100 for handling goods up to 100kg. Fixed control unit, On/Off switch, battery indicator and a separate battery charger.

| Article | M4600000 | M4600001 | M4600002 |
|--------------------|---------------------|--------------------|---------------------|
| Consists of | M4210023-03 + H9350 | M4210024-03+ H9350 | M4210025-03 + H9350 |
| Lifting capacity | 100 kg | 100 kg | 100 kg |
| Max lifting height | 1535 mm | 1735 mm | 2035 mm |
| Min lifting height | 140 mm | 140 mm | 140 mm |
| Dimensions LxBxH | 875x525x1870 mm | 875x525x2070 mm | 875x525x2370 mm |
| Lifting tool | Platform | Platform | Platform |
| Platform | 485x460 mm | 485x460 mm | 485x460 mm |
| Lifting speed | 100 mm/sec | 100 mm/sec | 100 mm/sec |
| Batteries | 2 x 7,5 Ah, 12V | 2 x 7,5 Ah, 12V | 2 x 7,5 Ah, 12V |
| Charging voltage | 100-240 V | 100-240 V | 100-240 V |
| Charger | 24 V, 1 A | 24 V, 1 A | 24 V, 1 A |
| Safety class | IP 41 | IP 41 | IP 41 |
| Wheel diameter | 75 / 100 mm | 75 / 100 mm | 75 / 100 mm |
| Material | Rfr, Alu, ABS | Rfr, Alu, ABS | Rfr, Alu, ABS |
| Extra | QCS | QCS | QCS |



TnT Handling USA, Inc.

Ph: 610-701-6350

Fx: 610-701-6354

E-mail info@tnthandling.com , Web www.tnthandling.com

HALLINS