# EASILY CONFIGURED TO MEET YOUR NEEDS

#### **FORK**

· Load platform

#### **POWER**

• Standard winch

#### BASI

• Standard base

### **WHEEL / CASTER OPTIONS**

- 8 in (20 cm) non-marking rear wheels
- Pneumatic 8 in (20 cm) rear wheels for rough terrain
- 2 in (5 cm) non-marking front swivel casters

### **OPTIONS & ACCESSORIES**

#### **PRODUCTIVITY**

- 8 in (20 cm) non-marking rear wheels
- Pneumatic 8 in (20 cm) rear wheels for rough terrain
- 2 in (5 cm) non-marking front swivel casters
- Field-installable foot break

## STANDARD FEATURES

#### **MEASUREMENTS**

- 5 ft 7 in (1.70 m) working height
- Up to 200 lb (91 kg) load capacity

#### **PRODUCTIVITY**

- Portable and compact design
- Lightweight durable aluminum construction
- High strength aircraft quality cable
- Cushioned neoprene hand grip
- Beveled aluminum platform for easy loading and unloading
- Portable folds for compact storage
- 8 in (20 cm) non-marking rear wheels
- Stair glides for easy handling on stairs
- Hold-down mechanism secures for transport

#### **POWER**

- Standard quiet high-speed winch
- Reversible winch handle for easy storage




## **Specifications**

MODEL	LOAD LIFTER™		
MEASUREMENTS	US	Metric	
⚠ Height - stowed	3 ft 9 in	1.14 m	
Height - platform maximum	5 ft 7 in	1.70 m	
🕒 Length - stowed	1 ft 3 in	.38 m	
Length - operating	2 ft 4.75 in	.73 m	
G Width - stowed	1 ft 8.5 in	.52 m	

PRODUCTIVITY		
Load capacity	200 lbs	91 kg
DLoad height minimum	2 in	.05 m
Ground clearance - center	.75 in	.02 m
Average cranks - standard winch	3 cranks/ft	3 cranks/.30 m
🔁 Load platform length	1 ft 2 in	.36 m
Description Load platform width	1 ft 4.75 in	.43 m

POWER	
Power source	reversible standard winch

WEIGHT*			
	65 lbs	29 kg	



<sup>\*</sup> Weight will vary depending on options and/or country standards.